



Refillable Ink Tank Printer with LCD Screen for Low-Cost Printing

This high-performance all-in-one printer combines low-cost printing with a backlit LCD screen for easy operation.

UP TO
8,100*
COLOUR PAGES

UP TO
7,600*
MONO PAGES
*Economy Mode



SEGMENT LCD

EASY, HASSLE-FREE INK REFILL

Ink refilling is now made easy. Each ink bottle nozzle is designed to fit seamlessly only into the designated ink tank, eliminating potential mixing accidents.



EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends the printer's lifespan even when printing in high volumes.



1.2" SEGMENT LCD PANEL

Easily navigate and configure printer settings using the LCD screen, which displays information at a glance.



SPECIFICATIONS / PIXMA G2770

PRINT	Maximum Printing Resolution		4800 (horizontal) ¹ x 1,200 (vertical) dpi	
	Print Speed ²	ESAT/Simplex (Mono/Colour)	11 / 6 ipm	
		FPOT Ready/Simplex (Mono/Colour)	9 / 14 sec	
		Photo (4 x 6")	45 sec	
SCAN ³	Scanner Type		Flatbed	
	Scanning Method		Contact Image Sensor (CIS)	
	Optical Resolution ⁴		600 x 1,200 dpi	
	Maximum Document Size		A4, LTR (216 x 297 mm)	
COPY	Copy Speed ⁵	Colour	sFCOT/Simplex	23 sec
			sESAT/Simplex	3.2 ipm
	Maximum Copies		20 pages	
	Maximum Document Size		A4, LTR	
PAPER HANDLING	Maximum Input Capacity	Plain Paper (64 g/m ²)	Up to 100 sheets	
		Photo Paper (4 x 6")	Up to 20 sheets	
	Media Size		A4, A5, A6, B5, LTR, LGL, Executive, Legal, Foolscap, F4, Oficio2, B-Oficio, M-Oficio, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 mm x 127 mm), Custom (width: 55 – 216 mm, length: 89 – 1,200 mm)	
Media Type		Plain Paper (64 – 105 g/m ²) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Glossy Photo Paper (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208, PS-808) Envelope		
SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility	Please visit https://asia.canon to confirm OS compatibility and to download the latest drivers.	Windows 11 / 10 / 8.1 / 7 SP1 ⁶ macOS 10.14.16 – 12 or later Chrome OS	
	Interface		USB 2.0	
	Canon Printing Apps		Easy PhotoPrint Editor, Creative Park, Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect	
	Power		AC 100 – 240 V, 50/60 Hz	
	Power Consumption ⁷		14 W (Standby: 0.6 W)	
	Duty Cycle		Up to 3,000 pages/month	
	Recommended Monthly Print Volume		150 – 1,500 pages	
	Operation Panel	Display	12" / 3.0 cm Segment LCD (Monochrome)	
	Dimensions (W x D x H)	Factory Configuration		416 x 337 x 177 mm
		Output/Trays Extended		416 x 557 x 268 mm
Weight		6.0 kg		
CONSUMABLES	Ink Bottles	Type/Colours	Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow	
		Page Yield ⁸ (A4, Pages)	GI-71 PGBK: 6,000 (Standard) / 7,600 (Economy ¹⁰) GI-71 C, M, Y: 7,700 ⁹ (Standard) / 8,100 ⁹ (Economy ¹⁰)	
User Replaceable Maintenance Cartridge		MC-G04		

Specifications are subject to change without notice.

¹ Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

² Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

³ TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.

⁴ Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available, only when you use TWAIN Driver.

⁵ Copy speeds are the average of sFCOT and sESAT. ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC 24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.

⁶ Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.

⁷ When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.

⁸ Page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the Standard ink bottles after initial setup. Page yield varies significantly depending on contents printed and other factors.

⁹ Based on 1 set of colour bottles.

¹⁰ The Economy mode reduces the ink consumption by lowering the density. More pages can be printed than the standard mode.



Delighting You Always

SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522

Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.