



Available in Red, Black and White



Made to *Impress*

Advanced Wireless All-In-One Printer with Intuitive 4.3" Touchscreen and Automatic Duplex Printing



4.3" TOUCH



AUTO 2-SIDED PRINT



BORDERLESS PHOTO PRINTING



DIRECT WIRELESS CONNECTION

Print from anywhere with cloud printing and scan to the cloud from your printer. Our top-of-the-line All-In-One photo printer meets all your family's demands with its six-ink system for stunning photos, easy connectivity, and stylish design.

COMPACT, SPACE SAVING FOOTPRINT

Designed for home use, this compact All-In-One printer fits into small spaces and shelves, offering convenience and efficiency for printing documents, photos, and creative projects.



INTUITIVE TOUCHSCREEN DISPLAY

Customise your printing experience with the versatile 4.3" touchscreen colour LCD, allowing quick access to frequently used features.



2-WAY PAPER FEEDING

Paper can be loaded for printing in 2 ways, via front cassette and rear feeding, eliminating the need to remove and reload paper stacks.



MOBILE AND CLOUD PRINTING

Print seamlessly from smartphones, tablets, laptops and cloud storage with the free Canon PRINT and Easy-PhotoPrint Editor apps.



SPECIFICATIONS / PIXMA TS8870

PRINT	Maximum Printing Resolution		4,800 (horizontal) ^{*1} x 1,200 (vertical) dpi	
	Print Speed ^{*2} (approx.)	ESAT/Simplex (Mono/Colour)	15 / 10 ipm	
		ESAT/Duplex (Colour)	3.0 ipm	
		Photo (4 x 6") (PP-201/Borderless)	13 sec	
Auto 2-Sided Printing		Yes		
SCAN ^{*3}	Scanner Type		Flatbed (Platen)	
	Scanner Technology		Contact Image Sensor (CIS)	
	Optical Resolution ^{*4}		2,400 x 4,800 dpi	
	Maximum Document Size		A4, LTR (216 x 297 mm)	
COPY	Copy Speed ^{*5} (approx.)	Colour	sFCOT/Simplex 7 ipm	
		ESAT/Simplex	14 sec	
	Maximum Copies		99 pages	
	Maximum Document Size		A4, LTR	
PAPER HANDLING	Maximum Input Capacity	Rear Tray	Plain Paper (64 g/m ²) Up to 100 sheets	
		Cassette	Plain Paper (64 g/m ²) Up to 100 sheets	
		Multi-Purpose Tray	1 sheet (Manual bypass)	
	Media Size	Rear Tray	A4, A5, B5, LTR, Card Size (91 x 55 mm), LGL, Envelope (COM10, DL), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 x 127 mm), Custom size (width: 55 - 215.9 mm, length: 89 - 676 mm)	
		Cassette	A4, A5, B5, LTR	
		Multi-Purpose Tray	120 x 120 mm	
		Borderless Printing ^{*6}	A4, B5, LTR, 4 x 6", 5 x 7", 7 x 10", 8 x 10", Card Size (91 x 55 mm), Square (89 x 89 mm, 127 x 127 mm)	
	Media Type	Rear Tray	Plain Paper (64 - 105 g/m ²), High Resolution Paper (HR-101N), Photo Paper Plus Glossy II (PP-201, PP-208), Photo Paper Plus Semi-Gloss (SG-201), Photo Paper Pro Luster (LU-101), Photo Paper Pro Platinum (PT-101), Premium Fine Art Rough (FA-RG1), Matte Photo Paper (MP-101), Double-Sided Matte Paper (MP-101D), Envelope	
		Cassette	Plain Paper (64 - 105 g/m ²)	
		Multi-Purpose Tray	Printable Disc	
Borderless Printing ^{*6}		A4, B5, LTR, 4 x 6", 5 x 7", 7 x 10", 8 x 10", Card Size (91 x 55 mm), Square (89 x 89 mm, 127 x 127 mm)		
NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility	Please visit https://asia.canon/support to confirm OS compatibility and to download the latest drivers. Windows 11 / 10 / 8.1 / 7 SP1 ^{*7} macOS 11.7.6 - 14 or later Chrome OS		
	Connectivity	Network	Wireless LAN IEEE802.11b/g/n	
		Interface	USB 2.0, Card Slot	
	Canon Printing Apps	Canon PRINT, Easy-PhotoPrint Editor, Creative Park		
	Mobile/Cloud Printing Solutions	Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect		
	Power	AirPrint, Mopria, Canon Print Service (Android), Direct Wireless, Cloud Service		
	Power Consumption ^{*8} (approx.)	AC 100 - 240 V, 50/60 Hz 27 W (Standby: 1.1 W)		
	Recommended Monthly Print Volume	80 - 300 pages		
	Operation Panel	Display	4.3" LCD Touchscreen	
	Dimensions (W x D x H)	372 x 345 x 142 mm		
Weight	6.6 kg			
CONSUMABLES	Ink Cartridges	Type/Colours	Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow, Black, Grey	
		Page Yield ^{*9}	Plain Paper	A4 Colour Documents ^{*10} : PGI-730 PGBK: 400 CLI-731 C, M, Y: 500 CLI-731 BK, GY: NA
			Photo Paper (PP-201)	4 x 6" Photos ^{*11} : PGI-730 PGBK: NA CLI-731 C, M, Y: 205 CLI-731 BK: 656 CLI-731 GY: 324

Specifications are subject to change without notice.

^{*1} Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
^{*2} Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
^{*3} TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
^{*4} Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available only when you use TWAIN Driver.
^{*5} Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.
^{*6} Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer and Photo Stickers
^{*7} Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.
^{*8} When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
^{*9} Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.
^{*10} Declared yield value in accordance with ISO/IEC 24711, using ISO/IEC 24712 colour chart. Values obtained by continuous printing. Black and grey dye-based inks are not used when printing under this condition. However, a minimal amount of black and grey dye-based ink is used for maintenance purposes.
^{*11} Declared yield value is in accordance with ISO/IEC 29102, using the ISO/IEC 29103 chart. Values obtained by continuous printing. Black pigment ink is not used when printing under this condition. However, a minimal amount of black pigment ink is used for maintenance purposes.



**SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
 CANON SINGAPORE PTE. LTD.**
 1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522
 Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.