

# Ceiling Mounting Kit CM10-VB

- This accessory is used for mounting camera to ceiling, supporting connection to junction box as well and  $\frac{3}{4}$ " NPS conduit pipe.
- Dimension: (H x W x D)  
178 x 134 x 253 mm  
(7.01 x 5.28 x 9.96 in.)
- Weight: Approx. 2300g (5.08lb.)
  - Impact Resistance: IK10 (20J)
- Compatible with Canon VB-R10VE, VB-R11VE, VB-R12VE and VB-R13VE



# Wall Mounting Kit WM10-VB

- This accessory is used to connect camera to the wall, supporting connection to junction box as well as  $\frac{3}{4}$ " NPS conduit pipe.
- Dimension: (H x W x D)  
234 x 134 x 245 mm  
(9.21 x 5.28 x 9.65 in.)
- Weight: Approx. 2300g (5.08lb.)
- Impact Resistance: IK10 (20J)
- Compatible with Canon VB-R10VE, VB-R11VE, VB-R12VE and VB-R13VE



# 1.5-Inch Pipe Adapter PA10-15-VB

- This accessory is an adapter used to connect camera to 1.5 Inch NPS pipe.
- Dimension: (H x W x  $\varphi$ )  
102 x 68 x  $\varphi$ 60 mm  
(4.02 x 2.68 x  $\varphi$ 2.36 in.)
- Weight: Approx. 200g (7.1oz)
- Compatible with Canon VB-R10VE, VB-R11VE, VB-R12VE and VB-R13VE



# Tinted Capsule DU10-S-VB

- This accessory is a replacement smoked capsule
  - Dimension: ( $\varphi$  x H)  
 $\varphi$ 179 x 108 mm  
( $\varphi$ 7.05 x 4.25 in.)
  - Weight: Approx. 145g (5.2oz.)
- Compatible with Canon VB-R10VE, VB-R11VE, VB-R11, VB-R12VE, VB-R13VE and VB-R13



# Hydrophilic Dome DU10-H-VB

- This accessory is a hydrophilic coated dome to replace existing dome to improve visibility in outdoor installation.
- Dimension: ( $\phi$  x H)  
 $\phi$ 179 x 108 mm  
( $\phi$ 7.05 x 4.25 in.)
- Weight: Approx. 145g (5.2oz.)
- Compatible with Canon VB-R10VE, VB-R11VE, VB-R12VE and VB-R13VE



# AC Adapter, PA-V18 (Optional)

▪ Dimension: (H x W x D) 32 x 60 x 130 mm (1.26 x 2.36 x 5.12 in.), excluding projections.

Weight: Approx. 245 g (8.7 oz.) (excluding power cable)

▪ Input: 100 – 240 V AC, 50/60 Hz

▪ Output: 13.1 V DC Max. 1.8 A (temperature:  $-10^{\circ}\text{C}$  –  $+35^{\circ}\text{C}$  ( $+14^{\circ}\text{F}$  –  $+95^{\circ}\text{F}$ )), 13.1 V DC Max. 1.1 A (temperature:  $-10^{\circ}\text{C}$  –  $+50^{\circ}\text{C}$  ( $+14^{\circ}\text{F}$  –  $+122^{\circ}\text{F}$ ))

▪ Operating Temperature:  $-10^{\circ}\text{C}$  –  $+50^{\circ}\text{C}$  ( $+14^{\circ}\text{F}$  –  $+122^{\circ}\text{F}$ )  
Humidity: 5% – 85% (without condensation)

▪ Compatible with Canon VB-M44/B, VB-M620D, VB-M620VE, VB-M720F, VB-H45/B, VB-H630D, VB-H630VE, VB-H730F MK II, VB-H651V, VB-H651VE, VB-H652LVE, VB-H761LVE, VB-H761LVE-H, VB-R11, VB-R10VE, VB-R11VE, VB-R13, VB-12VE, VB-R13VE, VB-M641V, VB-M641VE, VB-M741LE, VB-M741LE-H, VB-M50B

