

MSDS #:

Page 1 of 7 TC1787-0101

R04-9032

Product Code:

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE

COMPANY/UNDERTAKING

Product Name: Canon Cartridge 323 Magenta Starter (for Laser Beam Printer)

Product Code: R04-9032

Company Name: Canon Inc. Address: 30-2, Shimomaruko 3-Chome, Ohta-ku, Tokyo 146-8501, Japan

#04-01, Keppel Bay Tower, Singapore 098632 cspl_msds@canon.com.sg

Supplier: Canon Singapore Pte Ltd 1 HarbourFront Avenue,

Use of the Product: Toner for electrophotographic apparatus

SECTION 2 HAZARDS IDENTIFICATION

EU Classification: Not classified as dangerous.

Emergency Overview: Magenta fine powder, slight plastic odor.

Potential Health Effects and Symptoms:

Inhalation:

Exposure to excessive amounts of dust may cause physical irritation to respiratory tract.

Ingestion:

Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

Eye:

May cause transient slight irritation.

Skin:

May be non-irritant.

Chronic Effects:

Prolonged inhalation of excessive amounts of dust may cause lung damage. Use of this product as intended does not result in inhalation of excessive amounts of dust.

Medical Conditions Generally known to be Aggravated by Exposure:

Not determined

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS < Ingredient(s) > Chemical Name / CAS#/ Weight EU Symbol/ USA ACGIH TLV **EU ILV** DFG MAK EC# % **R-Phrase OSHA PEL** Generic Name Confidential 75-85 Not established Not established Styrene acrylate None/ None Not established Not established copolymer Wax Confidential 5-10 None/ None Not established Not established Not established Not established Not established Confidential 1-7 Not established Not established Not established Pigment None/ None Amorphous silica 7631-86-9/ 1-2 None/ None 20 mppcf, Not established Not established 4 mg/m^3 231-545-4 $80 \text{ (mg/m}^3)/\% \text{SiO}_2$ (Inhalable fraction)

< Carcinogen >

No component of this toner is listed as a human carcinogen or a potential carcinogen in IARC Monographs, NTP, OSHA regulations or Part 3 of Annex VI to Regulation (EC)1272/2008.

< PBT substance and vPvB substance >

No component of this toner is a PBT or vPvB subtance under Regulation (EC)1907/2006.

Revised: Date of Issue: January 30, 2009

MSDS #: Product Code: Page 2 of 7 TC1787-0101 R04-9032

SECTION 4 FIRST AID MEASURES

First Aid Measures:

Inhalation:

If symptoms are experienced, move victim to fresh air and obtain medical advice.

Ingestion:

Rinse mouth. Drink 1 or 2 glasses of water. If irritation or discomfort occurs, obtain medical advice immediately.

Eye:

Do not allow victim to rub eye(s). Flush with lukewarm, gently flowing water for 5 minutes or until particle is removed. If irritation persists, obtain medical attention.

Skin:

Wash with soap and water. If irritation persists, obtain medical advice.

Note to Physicians:

None

SECTION 5 FIRE FIGHTING MEASURES

Fire Fighting Measures:

Extinguishing Media:

CO2, water, dry chemicals

Unsuitable Extinguishing Media:

None

Special Fire Fighting Procedures:

None

Unusual Fire and Explosion Hazards:

Can form explosive dust-air mixtures when finely dispersed in air.

Fire and Explosive Properties (See also SECTION 9):

Hazardous Combustion Products:

CO2, CO

Other Properties:

Not available

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid breathing dust.

Environmental Precautions:

Do not wash away into sewer.

Method for Cleaning Up:

Sweep slowly spilled powder on to paper, and carefully transfer into a waste container. Clean remainder with wet paper, wet cloth or a vacuum cleaner.

If a vacuum cleaner is used, it must rate as a dust explosion-proof type. Fine powder can form explosive dust-air mixtures.

SECTION 7 HANDLING AND STORAGE

Handling:

Avoid breathing dust.

Use with adequate ventilation.

Storage:

Keep out of the reach of children.

Keep away from oxidizing materials.

Specific Uses:

Toner for electrophotographic apparatus.

For more information, please refer to the instruction of this product.

Date of Issue: January 30, 2009 Revised:

MSDS #: Product Code: Page 3 of 7 TC1787-0101

TC1787-0101 R04-9032

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

| Exposure Guidelines: | | | | | | | | |
|--|---|--|--|--|--|--|--|--|
| USA OSHA PEL (TWA): 15 mg/m³ (Total dust), 5 mg/m³ (Respirable fraction) ACGIH TLV (TWA): 10 mg/m³ (Inhalable fraction), 3 mg/m³ (Respirable fraction) DFG (MAK): 4 mg/m³ (Inhalable fraction), 1.5 mg/m³ (Respirable fraction) (Also refer to SECTION 3) | | | | | | | | |
| Engineering Controls: Use adequate ventilation. | | | | | | | | |
| Personal Protection Equipment(s): | | | | | | | | |
| Respiratory Protection: Required Not Required | | | | | | | | |
| Eye/Face Protection: Required Not Required | | | | | | | | |
| Skin Protection: ☐ Required ☐ Not Required | | | | | | | | |
| SECTION 9 PHYSICAL AND CH | EMICAL PROPERTIES | | | | | | | |
| Appearance: | Magenta fine powder | | | | | | | |
| Odor: | Slight plastic odor | | | | | | | |
| рН: | Not applicable | | | | | | | |
| Boiling Point/Range(°C): | Not applicable | | | | | | | |
| Melting Point/Range(°C): | 80-130 (Softening point) | | | | | | | |
| Decomposition Temperature (${}^{\circ}$ C): | > 200 | | | | | | | |
| Flash Point(°C): | Not applicable | | | | | | | |
| Flammable (Explosive) Limits: | Not applicable | | | | | | | |
| Autoignition Temperature(${}^{\circ}$ C): | Not available | | | | | | | |
| Flammability: | Not-flammable (Test method: Directive 92/69/EEC, A10 Flammability (Solids)) | | | | | | | |
| Explosive Properties: | Can form explosive dust-air mixtures when finely dispersed in air. | | | | | | | |
| Oxidizing Properties: | Not available | | | | | | | |
| Vapor Pressure: | Not applicable | | | | | | | |
| Vapor Density: | Not applicable | | | | | | | |
| Density / Specific Gravity: | 1.0-1.2 | | | | | | | |
| Water Solubility: | Negligible | | | | | | | |
| Fat Solubility: | Partially soluble in toluene and xylene. | | | | | | | |
| Partition Coefficient (n-Octanol/Water): | Not applicable | | | | | | | |
| Percent Volatile: | Negligible | | | | | | | |
| Evaporation Rate: | Not applicable | | | | | | | |
| Viscosity (mPa s): | Not applicable | | | | | | | |

Date of Issue: January 30, 2009 Revised:

MSDS #:

Page 4 of 7 TC1787-0101

Product Code: R04-9032

| SECTION 10 STABILITY AND | REACTIVITY |
|---|--|
| Stability: | Stable Unstable Unstable |
| Conditions to Avoid: | None |
| Materials to Avoid: | Strong oxidizers |
| Hazardous Decomposition Products: | CO, CO2 |
| Hazardous Polymerization: | ☐ May Occur ☑ Will Not Occur |
| Conditions to Avoid: | None |
| SECTION 11 TOXICOLOGICA | AL INFORMATION |
| Acute Toxicity: Inhalation: Not available | |
| Ingestion: Estimate: Rat, LD50 > 2000 mg. | /kg (See SECTION 16) |
| Estimate: Rabbit, transient slight | t conjunctival irritation only. (See SECTION 16) |
| Skin: Estimate: Rabbit, non-irritant (S | ee SECTION 16) |
| Sensitization: Estimate: skin: Non-sensitizing | (See SECTION 16) |
| Mutagenicity: Ames Test (S. typhimurium, E. o | coli): Negative |
| Reproductive Toxicity: Not available | |
| Carcinogenicity: Not available | |
| respirable-sized particles compa is most relevant to potential hum | response upon chronic inhalation exposure in rats to a toner enriched in red to commercial toner. No pulmonary change was found at 1 mg/m³ which han exposure. A minimal to mild degree of fibrosis was noted in 22% of the o moderate degree of fibrosis was observed in 92% of the animals at 16 |

 mg/m^3 .

These findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lung for a prolonged interval.

Revised: Date of Issue: January 30, 2009

MSDS #: Product Code: Page 5 of 7 TC1787-0101

R04-9032

| SECTION 12 ECOLOGICAL INFORMATION | | | | | | |
|---|---|--|--|--|--|--|
| Mobility: | Not available | | | | | |
| Persistence / Degradabilit | Not available | | | | | |
| Bioaccumulation: | Not available | | | | | |
| Ecotoxicity: | Estimate: Fish, 96h LL50 > 1000 mg/l (WAF) Estimate: Crustaceans, 48h EL50 > 1000 mg/l (WAF) Estimate: Algae, EbL50(72h), ErL50(0-72h) > 1000 mg/l (WAF) (See SECTION 16) | | | | | |
| Other Adverse Effects: | Not available | | | | | |
| SECTION 13 DISPO | SAL CONSIDERATIONS | | | | | |
| Method of Disposal: DO NOT put toner or toner container into fire; heated toner may cause severe burns. DO NOT shred a toner container, unless dust-explosion preventing measures are taken. Finely dispersed particles form explosive mixtures in air. Disposal should be subject to federal, state and local laws. | | | | | | |
| SECTION 14 TRAN | SPORT INFORMATION | | | | | |
| UN #: None | | | | | | |
| UN Shipping Name: None | | | | | | |
| UN Classification: None | | | | | | |
| UN Packing Group: None | | | | | | |
| Marine Pollutant: ☐ Ye ☐ No | ` ' | | | | | |
| Special Precautions: None | | | | | | |
| SECTION 15 REGU | LATORY INFORMATION | | | | | |
| < EU Information > | | | | | | |
| Information on the Labe | l: | | | | | |
| Symbol & Indication: | Not required | | | | | |
| R-Phrase: Not required | | | | | | |
| S-Phrase: | | | | | | |
| Not required | | | | | | |
| Dangerous Componer Not required | at(s): | | | | | |
| Special Precautions un Not required | nder 1999/45/EC Annex V: | | | | | |
| • | lation to Protection of Man or the Environment: | | | | | |
| 76/769/EEC: Not re | egulated | | | | | |
| (EC)2037/2000: Not regulated | | | | | | |
| (EC)689/2008: Not re | gulated | | | | | |
| Others: None | | | | | | |

Date of Issue: January 30, 2009 Revised:



MSDS #:

Page 6 of 7 TC1787-0101

R04-9032

Product Code:

| | TIC | | | | | |
|---|-----|----|------|----|------|-----|
| _ | | Λ. | Inta | mm | atio | n 🕆 |
| | | | | | | |

Information on the Label under OSHA:

Signal Word: Not required

Hazard warning:

Not required

Safety Advice:

Not required

Hazardous Component(s):

Not required

SARA Title III §313:

Chemical Name Weight %

None

California Proposition 65:

Chemical Name Weight %

None

< Canada Information >

WHMIS Controlled Product: Not applicable (Manufactured article)

< Australia Information >

Not classified as hazardous according to criteria of NOHSC. **Statement of Hazardous Nature:**

SECTION 16 OTHER INFORMATION

Estimate: Estimate based on test data on similar toner/developer/drum and/or the raw materials of this product.

Literature References:

- U.S. Department of Labor, 29CFR Part 1910
- U.S. Environmental Protection Agency, 40CFR Part 372
- U.S. Consumer Product Safety Commission, 16CFR Part 1500
- ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices
- U.S. Department of Health and Human Services National Toxicology Program, Annual Report on Carcinogens
- World Health Organization International Agency for Research on Cancer, IARC Monographs on the Evaluation on the Carcinogenic Risk of Chemicals to Humans
- DFG, List of MAK and BAT Values
- EU Directive 76/769/EEC, 67/548/EEC, 1999/45/EC
- EU Regulation (EC)2037/2000, (EC)689/2008, (EC)1907/2006, (EC)1272/2008
- Canada Workplace Hazardous Materials Information System
- Australia National Occupational Health and Safety Commission's Approved Criteria for Classifying Hazardous Substances[NOHSC:1008]

Revised: Date of Issue: January 30, 2009



MSDS #:

Page 7 of 7 TC1787-0101 R04-9032

Product Code:

Abbreviations:

EU: European Union.

OSHA PEL: PEL(Permissible Exposure Limit) under Occupational Safety and Health Administration (USA). ACGIH TLV: TLV(Threshold Limit Value) under American Conference of Governmental Industrial Hygienists.

EU ILV: Indicative Limit Values for Occupational Exposure under EU Directive 91/322/EEC, 2000/39/EC and 2006/15/EC.

DFG MAK: MAK(Maximale Arbeitsplatz-Konzentration) under Deutsche Forschungsgemeinschaft.

TWA: Time Weighted Average. STEL: Short Term Exposure Limit.

IARC: International Agency for Research on Cancer.

NTP: National Toxicology Program (USA). WAF: Water Accommodated Fraction

LL: Lethal Loading rate EL: Effective Loading rate

OSHA HCS: Occupational Safety and Health Act, Hazard Communication Standard (USA).

FHSA: Federal Hazardous Substances Act (USA).

WHMIS: Workplace Hazardous Materials Information System. NOHSC: National Occupational Health and Safety Commission.

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

The information, data and recommendations set forth herein (the "Information") are presented in good faith and are believed to be correct as of the date hereof. The company/manufacturer makes no representations as to the completeness or accuracy of the Information and disclaims responsibility for any reliance thereon. The Information is provided upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. Any use of the Information must be determined by the user to be in accordance with applicable Federal, state and local laws and regulations. In no event will the company/manufacturer be responsible for damages of any nature whatsoever resulting from the use or reliance upon the Information.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE WITH RESPECT TO THE INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS.

Date of Issue: Revised: January 30, 2009